ANTI – FATIGUE MAT INDEX

Grand Stand Deluxepage 2
Smooth Rubber Runnerpage 3
Marble Sof-Tylepage 4
Air Rugpage 5
Sof – Tred page 5

LYN Distributing

INDUSTRIAL MATS



Ideal for use in:

- •Banks
- Pharmacies
- •Labs
- ·Retail checkouts
- Mailrooms
- · Airports
- Factories

Grand-Stand Deluxe™

Grand-Stand Deluxe is available in 10 decorative colors to match any décor. The 3/32° thick rubber surface permanently bonded to a resilient natural rubber foam base provides excellent anti-fatigue capabilities. The mat also features beveled edges on all sides for an added extra measure of safety. Thermoset Vulcanized Rubber (SR) features 100% virgin synthetic rubber construction, greater flexibility and homogeneous color throughout. Your best choice for long-term wear.

Material: 3/32" Thermoset Vulcanized Rubber (SR) surface bonded to a 3/8" resilient rubber foam base

Thickness: 1/2*
Surface: Smooth
Characteristics: 1 1 1 1

Warranty: 2 year replacement warranty against defects in material and workmanship under normal usage and wear. Note: This warranty applies to identical replacement and does not cover damage from chairs, stools, tables, heavy

equipment, or high heels.

Marble Colors:



Solid Colors:



Item No.	Style	Size	Weight
Grand-Sta	nd Delu	xe™	
Standard Size	(lbs./ea.)		
238M1830	E	18" x 30"	7
238M2436	1	24" x 36"	11
238M1848	F	18" x 48"	11
238M3664	H	36" x 64"	29
Please specify	color.		
Standard Size	s, Solid		
238SO1830	E	18" x 30"	7
238502436	1	24" x 36"	11
238SO1848	F	18" x 48"	11
238503664	Н	36" x 64"	29
Please specify	color.		
Cut Lengths,	Marble (U	p to 60')	(lbs./sq. ft.)
238MC18		18" wide	1.8
238MC24		24" wide	1.8
238MC36		36" wide	1.8
238MC48		48" wide	1.8
Please specify	color.		
Cut Lengths,	Solid (Up	to 60')	
238SOC18		18° wide	1.8
238SOC24		24° wide	1.8
238SOC36		36" wide	1.8
238SOC48		48" wide	1.8
Please specify	color		




RUNNER & SPECIALTY MATTING

Smooth Rubber Runner™

Durable, smooth too runner is excellent for hospitals, schools, office buildings and other areas where durable floor is required. Available in 2 widths and 15 colors, meets or exceeds the federal specification SS-T-312B, Type II, sheet rubber.

Marble Colors:



Material: Thermoset vulcanized rubber (SR)

Thickness: 3/327

Characteristics: 11 11 11

Warranty: Standard warranty

Note: Rolls may be shipped in 2 pieces with the smaller being no less than 10'.

Cleaning Instructions: Sweep or vacuum daily to remove dirt and mop with mild detergent or floor cleaner. Avoid using high alkaline cleaners. Rinse immediately after mopping with clean warm water.

Solid Colors:



Smooth Rubber Runner™

Cut Lengths (Up to 60') (lbs./lin. ft.) 200C36 36" wide 2.25 200C48 48° wide 3.0 Please specify color.



Item No.	Size	Weight
Clear Vinyl		
Full Rolls		(lbs/ea.)
405R0027	27" x 60"	50
405R0036	36" x 60"	86
405R0048	48° x 60°	112
Cut Lengths (Up t	o 60°)	(lbs./ft.)
405C0027	2' wide	.83
405C0036	3' wide	1.43
405C0048	4' wide	1.87

Clear Vinyl

Heavy gauge clear vinyl mat protects carpets from wear and soil. Lets carpet or floor color show through while preventing wear and tear. Pointed grippers keep mat in place. Will not buckle, crawl or crack while tapered edges limits tripping. Recommended for use on low pile carpets. Surface wipes clean.

Material: Clear commercial gauge vinyl with

linear pattern and gripper back

Thickness: 3/16"

Surface: Herringbone pattern Characteristics: [2] [1] Warranty: Standard warranty

Color: Clear

Characteristics: Actual results may vary depending on the application and usage of the mat.








1 = excellent; 2 = good; 3 = fair; N = not rated.



MARBLE SOF-TYLETM

- Sales Tip: Easy to sweep clean or damp mop top surface.
 Recommended where there is a minimal amount of debris in the environment and a concern for the mat to match a décor.
- Where to Specify: Lab testing areas, Check-out counters, Order fulfillment lines.
- Smooth marble-pattern top surface of heavy-duty rubber is combined with dense closed cell foam base utilizing NOTRAX® exclusive UniFusion™ technology.
- UniFusion™ bond guaranteed for the life of the mat –
 See warranty for details
- Overall mat thickness is 1/2 inch.
- Sloped beveled foam on all 4 undersides affords easy access onto and off of mat.
- · Custom widths available













AIRUG® SOF-TRED™

- Sales Tip: Recommend the AIRUG® ribbed version for gripping features; SOF-TRED™ version for easy sweeping.
- Where to Specify: Work stations where anti-fatigue matting is needed at a low cost.
- Basic anti-fatigue protection provided through 2 versions of this Industry standard.
- PVC closed cell foam relieves leg and back discomfort; provides a barrier to cold floors.
- Overall thickness is 3/8 inch (Sof-Tred also available in 9/16")
- · All four sides are beveled to minimize trip hazards.





#410

STOCK SIZES	27" x 3'	27" x 5'	2' x 3'	3' x 5'	3' x 12'		
WEIGHT (lbs) 3/8" THICK	5	8	5	11	27		
WEIGHT (lbs) 9/16" THICK	N/A	N/A	7	16	37		
CUSTOM SIZES	2' × 60'	3' × 60'	4' × 60'	6' × 60'	2' Widths	3' Widths	4' Widths
WEIGHT (lbs) 3/8" THICK	85	130	170	275	0.70/sq.ft.	0.70/sq.ft.	0.70/sq.ft.
WEIGHT (lbs) 9/16" THICK	125	185	250	N/A	1.00/sq.ft.	1.00/sq.ft.	1.00/sq.ft.