



# EPOXIES



**EC-3 Heavy Coat Epoxy Resurfacer** - Resurface spalled or eroded concrete floors with this 100% solids, VOC compliant, two component epoxy. Designed for one coat application, at 12-20 mils, where chemical and abrasion resistance are needed. For use in a wide variety of industrial environments where low odor is required. EC-3 Heavy Coat Epoxy Resurfacer conforms to USDA guidelines for use in federally inspected meat and poultry plants. . [EC-3 TECHNICAL DATA SHEET](#)

**EC-3 Fast Cure Heavy Coat Epoxy Resurfacer** - Resurface spalled or eroded concrete floors with this 100% solids, VOC compliant, two component fast curing epoxy. Designed for one coat application, at 12-25 mils, where chemical and abrasion resistance are needed. For use in a wide variety of industrial environments where low odor is required. This product complies with restrictions on downtime due to its outstanding curing abilities. EC-3 Fast Cure Heavy Coat Epoxy Resurfacer conforms to USDA guidelines for use in federally inspected meat and poultry plants. [EC-3 FAST CURE TECHNICAL DATA SHEET](#)

**EC-4 Epoxy Patch** A three component, 100% solids, VOC compliant patching system designed for repairing and patching worn or eroded concrete floors in a variety of industries. It is especially effective in repairing areas subjected to the harsh effects of abrasive traffic and strong chemical spills. It is exceptionally tough, up to three times the strength of concrete, and is resistant to steel wheeled fork lift traffic. This product will not shrink as it cures. Cracks, holes and gouges may be patched from 1/4" thickness or greater. Packaged in pre-proportioned kits for error free jobsite mixing and application. EC-4 Epoxy Patch conforms to USDA guidelines for use in federally inspected meat and poultry plants. [EC-4 TECHNICAL DATA SHEET](#)

**EC-6 Self-Leveling Flooring** A three component, 100% solids, VOC compliant, 1/8" epoxy/aggregate system designed for a wide variety of industrial and commercial applications. This product has been formulated to resurface, level and restore heavily spalled and eroded concrete floors. Tough and dependable, EC-6 Self-Leveling Flooring counteracts the harsh effects of abrasive traffic and chemical spills. This product, when cured, produces a smooth glossy finish. EC-6 Self-Leveling Flooring conforms to USDA guidelines for use in federally inspected meat and poultry plants. [EC-6 TECHNICAL DATA SHEET](#)

**EC-7 Epoxy Shop Floor Resurfacer** - This versatile and economical, two-component, 100% solids epoxy coating can be used in a variety of applications. It can be used as a sealer or as an economical resurfacer under higher performing urethane and epoxy coatings at 5-10 mils. This product is also used as a binder for slurry and quartz systems. EC-7 Epoxy Shop Floor Resurfacer conforms to USDA guidelines for use in federally inspected meat and poultry plants. This product is also available in a fast curing version. . [EC-7 TECHNICAL DATA SHEET](#)

**EC-7 Fast Cure Epoxy Shop Floor Resurfacer** - A faster curing, two component, 100% solids version of EC-7 Epoxy Shop Floor Resurfacer. Can be ordered clear or prepigmented to "Oxford Gray". A variety of other colors are available with the use of UR-4 Color Add. [EC-7 Fast Cure TECHNICAL DATA SHEET](#)

**EC-8 Epoxy Primer Sealer** - A two component, solvent cut epoxy/polyamide primer/sealer that dries hard to a smooth glossy film. Dirt, dust, oils, and corrosive spills can be wiped away quickly and easily. [EC-8 TECHNICAL DATA SHEET](#)

**EC-10 HCR Topcoat** - Resurface spalled or eroded concrete floors with this 100% solids, VOC compliant, two component "novalac" epoxy. Designed for one coat application, at 10-16 mils, in areas subjected to extremely harsh chemical spills. Ideal for use in chemical processing and storage areas, as well as a wide variety of industrial environments where low odor is required. EC-10 HCR Topcoat conforms to USDA for use in federally inspected meat and poultry plants. [EC-10 TECHNICAL DATA SHEET](#)

**EC-11 Epoxy Aggregate Binder** - This 100% solids, VOC compliant, two component epoxy binder system is designed for patching/resurfacing and repairing worn and eroded concrete floors. Formulated to repair and protect concrete floor areas subjected to the harsh effects of high impact, abrasive traffic and strong chemical spills. This is not a complete system. It contains the hardener and resin base to be used with the aggregate of choice. It is an economy mortar binder for slurry or quartz systems. Mix with a graded aggregate and apply on the job at 1/8" to 1/4" or greater, to form a concrete patching and overlayment system. [EC-11 TECHNICAL DATA SHEET](#)

**LYN DISTRIBUTING**      965 North Redwood Road,      North Salt Lake, Utah. 84054  
Phone Salt Lake Area 295-5022      Outside Salt Lake Area 1-800-366-5022