

Although this product may be used on most surfaces, be sure to test before using.

CARPETS: To remove pet odors from carpets, rugs, or floors, pour diluted product directly on odor spot. Leave overnight. Use a clean white cloth to blot out product. If the odor persists, repeat the procedure.

UPHOLSTERY: To remove musty odors from upholstered couches and chairs, simply mist the fabric.

CARPET MACHINES: To deodorize carpets, add 1/4 cup each time the solution tank is refilled.


RESTROOMS: To deodorize urinals and bowls, spray surfaces and surrounding area including floors & walls.

LAUNDRY PRESPOTTER: Spray soiled areas with diluted product prior to washing. Leave overnight.

DRAIN LINES AND DOWN PIPES: Use product a minimum of two times weekly to a maximum of four times depending on the usage of the building. Add product in amounts listed, starting on the lowest floor and working up at the rate of one floor every day. Do not treat the same floor twice. When the top floor is reached, continue treatment on the top floor only.

Pipe Size	Dosage	Frequency
2"	4 ounces	twice/week
4"	8 ounces	twice/week
6"	12 ounces	twice/week
8"	16 ounces	twice/week

GREASE TRAPS: For traps less than 20 cubic feet capacity, add 4 to 5 ounces of product daily by pouring in a sink or pipeline closest to the trap. This should be done at night or when the traps are used the least. After adding, flush down with a cup of lukewarm water. For grease traps larger than 20 cubic feet, add 8 to 10 ounces daily using the same procedure.



Drainmate

**A LIQUID LIVING BACTERIA
DESTROYS WASTE AND ODOR THE
NATURAL WAY**

FOR USE ON:

***FLOORS AND WALLS • AROUND
TOILETS AND URINALS • RUGS &
CARPET STAINS • CLOTHING • BEDS •
PET WASTE BOXES.***

***RECOMMENDED FOR USE BY
HOSPITALS, RESTAURANTS, SCHOOLS,
NURSING HOMES, APARTMENTS,
KENNELS, HOTELS & MOTELS,
RECREATIONAL VEHICLES &
CHEMICAL TOILETS, INDUSTRIES,
PRISONS AND ANYWHERE ODORS
ORIGINATE!***

Contents:

Lyn Distributing
965 North Redwood Road
North Salt Lake, Utah 84054
Phone (801) 295-5022

SEPTIC TANKS: Add one pint per 25 cubic feet capacity for the initial treatment. Thereafter, use 8 ounces per week. This should be poured directly into toilet and flushed. If the septic tank has become clogged and odorous, add one gallon of product directly to the tank through the manhole.

MUNICIPAL SEWAGE TREATMENT TRICKLING FILTERS: Use 5 to 6 gallons per million gallons of daily flow. For preventive maintenance, use 2 gallons per MGD weekly to maintain proper operation.

RECREATIONAL VEHICLES & CHEMICAL TOILETS: Add 2 ounces per gallon of water in hold tank.

DRAIN OPENER ODOR CONTROL: This product may be used following the use of sulfuric acid based drain openers to dispel the odor of hydrogen sulfide gas.

SAFETY

Keep out of reach of children.

CAUTION: Contains emulsifiers. Undiluted product may cause eye irritation. Avoid contact with eyes. Avoid contact with open wounds.

FIRST AID: If splashed on skin, wash affected areas with soap and water. Remove contaminated clothing. If splashed in eyes, flush with large quantities of water. If swallowed, drink two glasses of water. Call a physician immediately.

NOTE: Do not subject product to disinfectants, hot or boiling water or chlorinated products.

Please Note: The use of this material being subject to conditions beyond the seller's control, seller's makes no warranty of any kind expressed or implied as to the material or its use. The user must assume all liability when using this product.