

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 435
IDENTITY: BUG BAN

Revision Date: 01/23/2003

Section I

| | | |
|----------------------|----------------------------|--------------------|
| Manufacturer's Name: | QUEST CHEMICAL CORPORATION | Telephone Numbers: |
| Address: | 12255 FM 529 | Emergency: |
| | NORTHWOODS INDUSTRIAL PARK | 800/255-3924 |
| | HOUSTON | Information: |
| State: | TX Zip Code:77041 | 713/8968188 |

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 2 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

| Name | Cas No. | OSHA PEL | ACGIH TLV | OTHER LIM | % |
|-------------------|------------|----------|-----------|-----------|-------|
| ISOPROPYL ALCOHOL | 67-63-0 | 400 PPM | 400 PPM | N/A | _____ |
| PROPANE/N-BUTANE | 68476-86-8 | 1000 PPM | 600 PPM | N/A | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

| | | | |
|-----------------------|------|----------------------------|------|
| Boiling Point: | 165F | Specific Gravity (water=1) | 0.89 |
| Vapor Pressure(mm Hg) | 70 | Melting Point: | N/A |
| Vapor Density(AIR=1) | 1 | Evaporation Rate: | 3 |
| Solubility in Water: | 0% | (Butyl Acetate=1) | |

Appearance and Odor: CLEAR SPRAY,MUSK ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used):>150F Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: CO2, FOAM, WATER, DRY CHEMICAL
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

