

# MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION	
<b>NFPA Rating:</b> Health-2; Flammability-4; Reactivity-0; Special-0 <b>Manufactured for:</b> LYN DISTRIBUTING <b>Address:</b> 965 N. Redwood Rd. North Salt Lake, UT 84054	<b>HMIS Rating:</b> Health-2; Flammability-4; Reactivity-0; Personal Protection-B <b>DOT Hazard Classification:</b> ORM-D <b>Identity (trade name as used on label):</b> LYN SPRAY ADHESIVE
<b>Date Prepared:</b> 03/22/93 <b>Prepared By:</b> STAN	<b>MSDS Number:</b> A165 <b>Revision:</b> 10
<b>Information Calls:</b> (801)295-5022 <b>EMERGENCY RESPONSE NUMBER:</b> 1(800)255-3924	<b>NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA</b>

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
METHYLENE CHLORIDE	75-09-2	Yes	100	50	a
HEXANE	110-54-3	No	500	50	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d
TOLUENE	108-88-3	Yes	300	100	d

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS	
<b>Boiling Point:</b> N/A	<b>Specific Gravity (H2O=1):</b> Concentrate Only = 1.1
<b>Vapor Pressure:</b> PSIG @ 70°F (Aerosols): Max.60	<b>Vapor Pressure (Non-Aerosols)(mm Hg and Temperature):</b> N/A
<b>Vapor Density (Air = 1):</b> N/E	<b>Evaporation Rate ( = 1):</b> N/E
<b>Solubility in Water:</b> Insoluble	<b>Water Reactive:</b> No
<b>Appearance and Odor:</b> Straw colored liquid with chlorinated solvent odor.	

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA			
<b>FLAMMABILITY</b> as per USA FLAME PROJECTION TEST (aerosols) <b>FLAMMABLE</b>	<b>Auto Ignition Temperature</b> N/E	<b>Flammability Limits in Air by % in Volume:</b> % LEL: N/E      % UEL: N/E	
<b>FLASH POINT AND METHOD USED (non-aerosols):</b> N/A		<b>EXTINGUISHER MEDIA:</b> Foam, dry chemical, carbon dioxide.	
<b>SPECIAL FIRE FIGHTING PROCEDURES:</b> Self-contained breathing apparatus.			
<b>Unusual Fire &amp; Explosion Hazards:</b> Do not expose aerosols to temperatures above 130°F or the container may rupture.			

SECTION 4 - REACTIVITY HAZARD DATA	
<b>STABILITY</b> <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE	<b>HAZARDOUS POLYMERIZATION</b> <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT    OCCUR
<b>Incompatibility (Mat. to avoid):</b> Strong oxidizing agents, reactive metals such as aluminum, magnesium and sodium.	<b>Conditions to Avoid:</b> Open flame, welding arcs, heat, sparks.
<b>Hazardous Decomposition Products:</b> CO, CO2, HC1, small amounts of phosgene and chlorine.	

SECTION 5 - HEALTH HAZARD DATA
<b>PRIMARY ROUTES OF ENTRY:</b> <input checked="" type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input type="checkbox"/> SKIN ABSORPTION <input type="checkbox"/> EYE <input type="checkbox"/> NOT HAZARDOUS
<b>ACUTE EFFECTS:</b> <b>Inhalation:</b> Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness. <b>Eye Contact:</b> Irritation. <b>Skin Contact:</b> Irritation.
<b>Ingestion:</b> Unlikely route of exposure. Possible chemical pneumonitis if aspirated into lungs.
<b>CHRONIC EFFECTS:</b> (Effects due to excessive exposure to the raw materials of this mixture) May cause elevated carboxyhemoglobin levels, salivary gland tumors, kidney and lung damage, liver abnormalities.
<b>Medical Conditions Generally Aggravated by Exposure:</b> May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES
<b>Eye Contact:</b> Flush with water for 15 minutes. If irritated, seek medical attention.
<b>Skin Contact:</b> Wash with soap and water. If irritated, seek medical attention.
<b>Inhalation:</b> Remove to fresh air. Resuscitate if necessary. Get medical attention.
<b>Ingestion:</b> DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES
<b>Respiratory Protection (specify type):</b> If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.
<b>Protective Gloves:</b> Rubber gloves. <b>Eye Protection:</b> Safety glasses recommended.
<b>Ventilation Requirements:</b> Adequate ventilation to keep vapor concentration below TLV.
<b>Other Protective Clothing &amp; Equipment:</b> None
<b>Hygienic Work Practices:</b> Wash with soap and water before handling food. Remove contaminated clothing.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE
<b>Steps To Be Taken If Material Is Spilled Or Released:</b> Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. Allow solvents to evaporate. Clean up adhesive with sawdust. DO NOT FLUSH TO SEWER.
<b>Waste Disposal Methods:</b> Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.
<b>Precautions To Be Taken In Handling &amp; Storage:</b> Do not puncture or incinerate containers. Do not store at temperatures above 130°F.
<b>Other Precautions &amp;/or Special Hazards:</b> KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.

*We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.*

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only