MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MAI	NUFACTU	JRER'S INFORMAT	TION				
IFPA Rating: Health-1; Flammability-4; Reactivity-0; Special-0 HMIS Rating: Health-1; Flammability-4; Reactivity-0; Personal Protection-B							
Manufacturer's Name: AMREP, INC.	OT Hazard Classification: ORM-D						
Address: 990 Industrial Park Drive, Marietta, GA 30062	lde	dentity (trade name as used on label):					
Manufactured for-Lyn Dist.		GUM REMOVER					
,		MSDS Number: 183 & A123 Revision- 3					
Information Calls: (801) 295-5022		NOTICE: JUDGEN		SED ON IN	DIRECT TE	ST DATA	
EMERGENCY RESPONSE NUMBER: 1(800)255-3924		NOTICE. CODOLI		.025 011 111	DIREO! IE	.01 57(17)	
	IDENTIEL	CATION AND INC	DMATIC	. NI			
SECTION 1 - MATERIAL	IDENTIFI						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA III LIST	OSHA PEL	ACGIH	Carcinogen Ref. Source **	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater) ISOBUTANE / PROPANE BLEND		75.00.5		(ppm)	TLV (ppm)		
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d	
		74-98-6	No	1000	1000	d	
			-		 		
					<u> </u>		
SECTION 2 - PHYSICA							
Boiling Point: N/A	coiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.5379						
Vapor Pressure: PSIG @ 70°F (Aerosols): 70 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature):					erature): N/A		
Vapor Density (Air = 1): N/E	vaporation Rate (= 1): N/E						
Solubility in Water: Slight	Wa	ter Reactive: No					
Appearance and Odor: Clear, odorless spray.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
FLAMMABILITY as per USA FLAME PROJECTION TEST	Auto Ig	uto Ignition Temperature Flammability Limits in Air by % in Volume:					
(aerosols) EXTREMELY FLAMMABLE		N/E	% LEL	.: 2.0	% UE	L: 10.0	
FLASH POINT AND METHOD USED (non-aerosols): N/A	EX.	TINGUISHER MEDIA:	Foam, dr	chemical, ca	bon dioxide, v	vater.	
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing					,		
apparatus.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X]WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Strong oxidizing agents. Conditions to Avoid: Open flame, welding arcs, heat.							
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION []SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness. Vapors							
are heavier than air and displace oxygen required for breathing. Eye Contact: May cause burns and frostbite. Skin Contact: May cause burns and frostbite.							
Eye Contact: May cause burns and frostbite. Skin Contact: May cause burns and frostbite. Ingestion: Unlikely route of exposure.							
CHRONIC EFFECTS: Unknown.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention. If frostbitten, warm skin slowly.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. Give oxygen.							
Ingestion: Unlikely route of exposure.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH to be used in a positive pressure mode.							
Protective Gloves: Rubber gloves recommended. Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Ventilate area to disperse vapors. DO NOT FLUSH TO SEWER. Remove ignition sources.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pre-							
Precautions To Be Taken In Handling & Storage: Do not puncture or in					n°F		
						and with alder	
Other Precautions &/or Special Hazards:KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Avoid contact with skin or							
eyes.							

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

^{**} Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only