## MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFAC	CTUR	ER'S INFORMAT	ION				
NFPA Rating: Health-3; Flammability-1; Reactivity-1; Special-0	HMIS Rating: Health-3; Flammability-1; Reactivity-1; Personal Protection-B						
Manufacturer's Name: LYN DISTRIBUTING	DOT Hazard Classification: ORM-D						
Address: 965 NO. REDWOOD ROAD	Identity (trade name as used on label):						
NO. SALT LAKE, UTAH 84054		MOISTURE GUARD					
Date Prepared: 03/22/93 Prepared By: STAN	MSDS Number: A129 Revision- 12						
Information Calls: (801) 295-5022	NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA						
EMERGENCY RESPONSE NUMBER: 1(800)366-5022							
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION							
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES  CAS Number SARA OSHA PEL ACGIH Carcinogen							
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)  CARBON DIOXIDE		124-38-9	III LIST No	(ppm) 5000	TLV (ppm) 5000	Ref. Source **	
METHYL CHLOROFORM		71-55-6	Yes	350	350	d	
PETROLEUM DISTILLATE		64742-54-7	No	5mg/M3	5mg/M3	d	
BARIUM PETROLEUM SULFONATE		61790-48-5	No	5mg/M3	5mg/M3	d	
5//// 12/// 0220 m 002/ 0//// 2		01790-40-5	INU	3HIg/W3	5HIG/W3	u	
CECTION 2 PHYSICAL (CH	FMIC	AL CHARACTER	ICTICC				
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS  Boiling Point: N/A   Specific Gravity (H2O=1): Concentrate Only = 1.21							
Vapor Pressure: PSIG @ 70°F (Aerosols): 85-100	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A						
Vapor Density (Air = 1): N/E	Evaporation Rate ( = 1): N/E						
	Water Reactive: No						
Appearance and Odor: Light brown liquid, with chlorinated solvent odor.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
FLAMMABILITY as per USA FLAME PROJECTION TEST Aut	to Iani	tion Temperature	Flamm	ability Limits	in Air by % i	n Volume:	
(aerosols) NON-FLAMMABLE	N/E % LEL: N/E % UEL: N/E						
FLASH POINT AND METHOD USED (non-aerosols): N/A	EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.						
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing							
apparatus.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Strong oxidizing agents, reactive metals such as aluminum and magnesium.  Conditions to Avoid: Open flame, welding arcs, heat.							
Hazardous Decomposition Products: CO, CO2, HC1, small amounts of phosgene and chlorine.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION []SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Mild irritation.  Skin Contact: Mild irritation due to defatting of skin.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or							
lung damage.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention. Never give anything by mouth to an							
unconsciousness person.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.							
Protective Gloves: Neoprene if skin easily irritated. Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal							
regulations.DO NOT FLUSH TO SEWER.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.							

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

<sup>\*\*</sup> Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only