55 GALLON

Version 1.0 Date 08/01/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : FORMULA 300 CLEANER 55 GALLON

Material number : K 1058

Manufacturer or supplier's details

Company : Lyn Distributing

Address : 965 North Redwood Road

North Salt Lake, Utah 84054

Telephone : 801-295-5022

Emergency telephone numbers

For SDS Information : Compliance Services 1-801-295-5022
For a Medical Emergency : 801-201-1135 All Calls Recorded

For a Transportation : 801-201-1135 - All Calls Recorded.

Emergency

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Color	Blue clear
Odor	mild

GHS Classification

Skin corrosion : Category 1A Serious eye damage : Category 1

GHS Label element

Hazard pictograms

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/

shower.

55 GALLON

Version 1.0 Date 08/01/2022

P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

Potential Health Effects

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	>= 5 - < 20
sodium xylene sulphonate	1300-72-7	>= 1 - < 5
sodium metasilicate penetahydrate	6834-92-0	>= 1 - < 7

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

55 GALLON

Version 1.0 Date 08/01/2022

wounds from corrosion of the skin heal slowly and with

difficulty.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Sulphur oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

recautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Neutralise with acid.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

55 GALLON

Version 1.0 Date 08/01/2022

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from oxidising agents and strongly acid or alkaline

materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA TWA	20 ppm 5 ppm 24 mg/m3	ACGIH NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure	200 mg/g	ACGIH BEI
				ceases)		
Remarks: Creatinine						

Personal protective equipment

55 GALLON

Version 1.0 Date 08/01/2022

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : blue clear

Odor : mild

Odor Threshold : no data available

pH : 12.5 - 13.5

Melting point/freezing point : no data available

Boiling point : 104.44 °C

Flash point :

does not flash

Evaporation rate : 1

Upper explosion limit : no data available

Lower explosion limit : no data available

Vapour pressure : not determined

Relative vapour density : no data available

Density : 1.021 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: no data available

Auto-ignition temperature : not determined

Thermal decomposition : no data available

Viscosity

Viscosity, kinematic : 5.7 mm2/s (20 °C)

55 GALLON

Version 1.0 Date 08/01/2022

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

: No decomposition if stored and applied as directed.

: no data available

Incompatible materials : Acids

Oxidizing agents

Hazardous decomposition

products

: Carbon dioxide (CO2) Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 2,129 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 40 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 4,869 mg/kg

Method: Calculation method

Components:

disodium metasilicate:

Acute oral toxicity : LD50 rat: 1,153 mg/kg

Skin corrosion/irritation

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

no data available

55 GALLON

Version 1.0 Date 08/01/2022

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

2-butoxyethanol: sodium xylene sulphonate: sodium metasilicate:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

: Remarks: no data available

Mobility in soil

no data available

Other adverse effects

no data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

55 GALLON

Version 1.0 Date 08/01/2022

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International regulation

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

not applicable

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

55 GALLON

Version 1.0 Date 08/01/2022

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

All components of this product are on the Canadian DSL.

AICS
On the inventory, or in compliance with the inventory

NZIoC
On the inventory, or in compliance with the inventory

PICCS
On the inventory, or in compliance with the inventory


IECSC
On the inventory, or in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information



Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA GHS Label Information:

Date 08/01/2022 Version 1.0

Hazard pictograms



Signal word Hazard statements Precautionary statements

Causes severe skin burns and eye damage.

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ show er. IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance organization supporting this manufacturer, supplier or distributor.